DirecTrailer

48 ft. All-Steel Flatbed Spring Slider

Main Beams	130 Ksi 7/16”x 5” top and bottom flanges welded continuously to both sides of 3/16” one piece 80Ksi web. Beam tapers to provide a 55” loaded rear deck height. 11 5/8” gooseneck depth.
Frame Capacity	80,000# distributed frame rating - GAWR and tire ratings determine legal payload.
Fifth Wheel Height	Kingpin Height - 49” unloaded.
Dimensions	Width – 102” Total length - 48 Ft.
Front Skirt	Steel construction with diagonal corners; 4 welded on pockets for bulkhead. Air and light connectors offset roadside.
Rear Skirt	Steel rear with 5 stake pockets mounted internally. Dock bumpers on corners for protection. Bolt-on removable steel bumper
Side Rails	7/32” 80Ksi Rolled formed side rails at 6.8#’s per foot. Double spools and stake pockets located on 24” centers with 2 1/2”x 3/8” rub rail. Double LL aluminum winch track roadside with 12 sliding winches.
Flooring	1 1/8”Apitong flooring, finger-jointed full length, ship lapped, secured with 2 coated 5/16” screws staggered per crossmember.
Crossmembers	4” Steel I-Beam on 12” centers, 3.19# per foot; T-1 (100KSI) flanges; 80 Ksi web. Built like a main beam.
Side Rail Knee Braces	Steel fabricated diagonal braces for maximum support. Four (4) per side on 48’ length.
Landing Gear	Austin-Westran 2 Speed, with 10”X10” cushion foot shoes. Heavy duty steel bracing in two directions for support and stability. *Speedy Crank* for easy raising and lowering
Kingpin and KP plate	Double spool set at 30” from front. Tapered, reinforced KP plate- 5/16” steel.
Suspension Brakes & Axles	Hutch 3-leaf spring Suspension with Hutch Slider Box, 60” travel, 4 pins, 6” increments. Wabco 2S/1M wired to center pin of seven way socket.
Wheels	8.25 X 22.5 hub-piloted steel disc
Tires	295/75R 22.5 14 ply
Electrical System	Phillips Sealed harness with 7 way plug, Grote LED lights; 3 markers per side; 3 stop, turn and tail lights per side on rear. Incandescent bracket mounted mid-turn signals
Paint	Completely shot blasted, cleaned, pre-primed then primed with premium zinc epoxy primer and painted complete with premium true 2-part urethane.
Mud Flaps	Gorilla Mud Flaps